



FUEL STORAGE AND DISPENSING EQUIPMENT SOLUTIONS

476 Boundary Road, Derrimut, VIC, 3026

03 9311 7822



Our Liquip Rural Range

If you're after high quality and reliable fuel dispensing equipment, at an affordable price, then you can rely on Liquip Rural and our distributors.

Not only do we stock and sell Piusi and OPW, we can also support you with expert advice and knowledge on what product works best for the requirement, saving you time and money on your fuel dispensing solution.

Diesel and Petrol Bowsers



www.liquipvictoria.com.au

<u>Piusi Pumps</u> 240V AC Pumps

Safely and Quickly Transfer Hydrocarbons and Other Bulk Liquids Via Our Range of Leading Transfer Pumps and **Dispensing Units.**



Piusi Panther 72 Diesel Pump (240V)

- Self Priming Rotary Vane Pump
- Flow Rate Up to 72 L/min
- Bypass Valve and Thermal Motor Overload Protection
- Suction Strainer
- Suitable for Diesel and Fixed Transfer Systems
- 90 L/min also available



Piusi ST 200 AC Diesel **Transfer Dispensing Pump**

- Flow Rate Up to 200 L/min
- Accuracy ± 1% With Oval-Gear Flow Meter (on reauest)
- Light Weight and Possibility of Fitting Wheels (Portable)
- **ON/OFF** Switch
- Continuous 240V AC Operation



Piusi E120 Diesel AC Pump

- Flow Rate Up to 100 L/min
- Continuous AC Operation
- Noise Level Below 70 dB
- Electric Pump
- Fitted with By-Pass Valve and Elevated Reliability Seal Even at Low Temperatures
- 240V AC Continuous Duty
- **Thermal Protection**

LV-F00395010



Piusi EX140 Diesel & Petrol **Transfer Pump**

- Suitable for Transfer of Petrol & Diesel
- High Flow Rate Up to 140 L/min
- Heavy Duty
- Continuous Duty

LV-F00321000

PIUSI

Transfer Pump

Cast Iron Impeller

For Diesel Fuel Use

Piusi E300 AC Diesel

Self Priming Electric Pump

2 Metre Cable with Socket

2" Inlet/Outlet Connections

High Flow Rate (Up to 550 L/min)

Continuous Duty with 240V Power Supply

- Thermal Protection
- ATEX/IECEx Certified
- AC Voltage Power

LV-F0037601B



Piusi EX50 Drum

- Tank Top 240V AC ATEX/IECEx Certified Pump (Flammable Liquids)
- Suitable for Petrol, Kerosene and Diesel
- High Efficiency Pump (50 L/min)
- Meter Approval (Flammable Liquids)
- 4 Metre Hose, Automatic ULP Nozzle
- Inlet Strainer and Pressure Relief Valve
- 2" BSP Quick Coupling (telescopic suction tube)
- Anti-Noise Filter

LV-F00395050 \$1,121.82 Incl. GST PIUSI

Piusi E140 Diesel Transfer Pump

- Heavy Duty, Electric Pump For Diesel Transfer
- Versatile and Suitable For Different Industries Including Automotive, Agriculture, Transport, Garage and Construction Use
- High Flow Rate Up to 140 L/min
- Continuous Duty and Sturdy Design
- Reliable in Low Temperature Conditions
- 240V AC

FOLLOW US ON

\$1,264⁴⁶

240V Fuel Pumps Are Ideal For Fixed Location, **High Volume Fuel** Transfer – and a Popular Choice with Today's Fuel Management Systems.







AdBlue Pumps

LV- F00206010

\$809.30 Incl. GST PIUSI

Piusi Squalo 35 AC Submersible AdBlue Pump

- Flow Rate Up to 35 L/min
- **Regenerative Turbine**
- Designed for Use in AdBlue Storage Tanks
- Integrated Pressure Regulator
- Reduced Energy Consumption Model
- 30mm Dead Level Ability
- Can be Used for Water Transfer

12/24V DC Pumps

LV-F0020303B

\$539.54 Incl. GST

Piusi Suzzarablue AdBlue Pump (240V)

- Pump Diaphragm (Self Priming)
- 3/4" Hose Tail Connection
- Flow Rate Up To 35 L/min
- **ON/OFF** Switch Þ
- 2 Metre Electrical Lead With 3 Pin 10 AMP Plug
- Suitable for AdBlue and Water



PIUSI Piusi AdBlue IBC Pump Kit 240V AC

PIUS

- Flow Rate Up to 35 L/min
- Suzzarablue Diaphragm
- AC/DC Voltage
- ±1% Accuracy
- 20min Duty Cycle
- Nozzle (Auto or Manual), Suction and 6 Metre Hose Included

1640-

Flow Meter Available on Request

LV-F0022400C

\$473.61

24V Diesel Transfer Pump -Carry 3000 Kit

PIUSI.

- Flow Rate Up to 50 L/min 24V Pump with 2m Hose and Manual Nozzle
- Mobile Diesel Transfer Pump
- Contains Leads and Clamps
- 30 Minute Continuous Duty Cycle
- 3/4" BSP Connection
- Long Lasting Application

\$1,217^{.02} Piusi 12V Diesel Transfer

- **Bi-Pump with 4m Cable** Flow Rate Up to 85 L/min
- 12V DC Operation

LV-F0036302A

- By-Pass Valve Incorporated into the Pump Body
- 30 Minute Duty Cycle
- Vane Pump with Rotor
- 1" BSP Flanged Inlet/Outlet Ports
- Sturdy Structure and Compact Design



Dispensing Package

- 12V DC Heavy Duty Drum Bi-Pump
- Flow Rate Up to 80 L/min
- 1" BSP Inlet

LV-F0036304A

PIUSI

and Clamps

Cable

Piusi 24V Diesel

Flow Rate Up to 85 L/min

1" BSP Flanged Inlet/Outlet Ports

Sturdy Structure and Compact Design

- Piusi K33 Mechanical Meter (3 digit)
- Diesel Automatic Nozzle and Holster Attached to 4 Metre Diesel Delivery Hose
- Cable with Battery Clamps
- **Telescopic Suction Tube**

LV-F00212000 \$3,338.38 Incl. GST PIUSI 5

Piusi Pitstop DC Diesel Transfer Pump

- Flow Rate Up to 45 L/min
- Automatic Hose Reel with 14 Metres of Hose
- Automatic Nozzle
- 3/4" Diesel Hose
- Side Safety Guards
- Ready to Install
- Built in DC Pumps

12V DC Cast Iron Pump (Fixed Brush Motor) 2 Metre Suction Ability

- 4 Metre x 3/4" Diesel Delivery Hose With Manual
- Nozzle (Swivel)
- Suction Strainer
- Flow Rate up to 50 L/min
- Compact and Suitable for Ute Storage Tanks

www.liquipvictoria.com.au

Transfer Bi-Pump with Leads

24V DC Operation c/w On/Off Switch and 4m

By-Pass Valve Incorporated into the Pump Body

\$1,179^{.69}

LV-F0022500C

\$557.91 Incl. GST

Piusi Portable Diesel

Dispensing Pump

with 2 Metre Power Cable and Battery Clamps

Flow Meters

Electronic Meters

Digital Figure Display For 21st Century Bulk Liquid Transfers.



Piusi K24 AdBlue

Electronic Meter

- Flow Rate: 20-120 L/min
- 1" BSP Connections
- Accuracy ±1%
- 5 Digit Resettable and 6 Digit Totaliser
- Display Rotatable to 4 Different Positions
- Supplied with Batteries
- Install In Line at Pump or Nozzle
- Suitable for Water or AdBlue Transfer



Electronic Meter

- Flow Rates 7 120 L/min
- Aluminium Body
- 1" BSP Connections
- Accuracy ±1% 5 Digit Partial and 6 Digit Total
- Repeatability 0.3%
- Suitable for Low Viscosity Fluids
- On Request: UL Classified, ATEX/IECEx or Pulser Version

LV-F00472A00 PILSI **Piusi K600/3**

Electronic Meter

Flow Rate Up To 100 L/min

- Non-Commercial Dispensing of Low, Medium and High Viscosity Fluids (including Diesel, Lubricating Oil and Other Special Fluids Compatible With Construction Materials)
- 1" BSP Connection
- Accuracy ± 0.5%
- 5 Digit Partial Total and 8 Digit Non Resettable Total

Mechanical Meters





Piusi K700 Pulse Meter

- Flow Rate 25 to 250 L/min
- Fluid Viscosity: 5 5000 cSt
- Pulses: 14 /L

LV-F0049800A

- Oval Gear Pulse Meter
- Measures Transfer of Diesel, AdBlue and Oils

\$1,811^{.58}

\$2,173.90 Incl. GST

- No Electronic Display
- Accuracy ± 0.5% After Calibration
- Max Fluid Temperature: ±60°
- 2" BSP Flanged Inlet and Outlet

\$673.75 Incl. GST



- Accuracy ± 1%
- Petrol ATEX Approved
- 1" BSP Inlet and Outlet
- Suitable For Biodiesel, Diesel or Oil
- 3 Digit Resettable and 6 Digit Totaliser
- Works With Gravity Feed Tanks or 12/24V DC
- and 240V AC Pumps
- Petrol Version Also Available

LV-560000 PIUSI \$514.59

Piusi K44 **Mechanical Meter (4 Digit)**


- Flow Rate 20 to 120 L/min
- 4 Digit Resettable and 7 Digit Totaliser
- 1" BSP Inlet and Outlet
- Accuracy ± 1%
- Suitable for Diesel, Biodiesel or Oil
- Works with Gravity Feed Tanks or 12/24V DC and 240V AC Pumps
 - **FOLLOW US ON**

- LV-F00540000
 - <u> PIUSI</u>

Piusi K700 Diesel **Mechanical Meter**

- Flow Rate 40 to 220 L/min
- 4 Digit Partial Totals and 7 Digit Totals
- Accuracy ± 1.5%
- Repeatability 0.3%

- Max. Operating Pressure 10 Bar (142 psi)
- For Medium to High Flow Rates
- No Battery Needed
 - 11/2" BSP Inlet and Outlet



00473000

PILS

Electronic Meter

Flow Rate 15-150 L/min

11/2" BSP Flanged Inlet and Outlet

Piusi K600/4

Accuracy ± 0.5%



LIQUIP

RURAL

Benefits of Having the Right **FMS** Include: Improved Fuel Management and Efficiency, Ease of Information Access and Accurate Calculation of Taxes.





Piusi MC Box FMS

- Multi-User Control Panel with Accessories for PC Connection
- Dual Display, Keyboard and i-Button reader Up to 120 Users
- Pre-Selection of Dispensed Quantity
- Software Package Separate (See Below)
- Calculates Consumption of Each Individual User"



POA Smart

SmartFill Gen 2 FMS

- Can Easily be Adapted to Any Bulk Liquid Storage Application
- No Ongoing Costs
- No PC Software Requirement
- Cloud Based Technology
- Can be Used for Mining, Transport, Marinas, Service Vehicles etc.
- **NMI** Approved



Smart Fill

SmartFill Outdoor Payment Terminal (OPT)

- Makes Unattended Fuel Sales Easy
- Large Display
- Easy to Instal

1290L-075L

Nozzle

- Supports All Major Credit and Debit Cards
- Works with All Popular Pump Brands Built on Top of SmartFill Gen 2 Modular
- Kitset Code: SWAREZ with Web- LV-F00773210 or USB- LV-F00773010 \$1,566^{.48}

FMS Software Kit

- Contains Software, Managers Key, 10 Yellow Fob Keys and Key Reader
- Stores All Refuelling Transactions Recorded From the Pump
- Allows Data to be Transferred Directly to a PC Suitable for the Cube 70MC, Self Service MC, Self Service FM and the MC Box Fuel
- Management Systems Software Is Available as USB or Web Version



Piusi Access 85

- Up to 85 Users
- Smart Control of the Withdrawal of Fuel by Numerous Users
- Can Control: Pump Start/Stop, User Access, Þ Position of Dispenser Gun
- Features Emergency Stop Button When Connected to OCIO, Can Detect
- Minimum Tank Level and Block the Pump Driver Key Extra

Fuel Pump Accessories

POA



High Flow Nozzle - 210 1¹/₄"

- For High Flow, Bulk Fuel Oil Delivery Service
- Lightweight Aluminium Body
- Replaceable Hold Open Rack
- Non Adjustable Dash Pot to Minimize Closing Line Shock
- Optional 296 Brass or 297 Aluminum Spout
- 50 psi (3.45 Bar) Maximum Pressure
- 1 1/4" Male Connections



High Flow Nozzle - 210 1¹/₂"

- For High Flow, Bulk Fuel Oil Delivery Service
- Lightweight Aluminium Body
- Replaceable Hold Open Rack
- Non Adjustable Dash Pot to Minimize Closing Line Shock
- Optional 296 Brass or 297 Aluminum Spout
- 50 psi (3.45 Bar) Maximum Pressure 1 1/2" Male Connections

CONTACT US: 03 9311 7822

One-Hand Control of Hold-Open Mechanism

For Heavy-Duty, High-Flow Truck, Bus and

Venturi-Type Shut-Off Mechanism - for

1290 Automatic Shut-Off

Home Fuel Oil Delivery Service

Aluminium Body - Lightweight

Built-In Outlet Check Valve

Automatic Shut-Off

sales@liquipvictoria.com.au

www.liquipvictoria.com.au

\$78.70 Incl. GST

Automatic Nozzle - 19DEF

- DEF / AdBlue Compatibility
- Proven OPW Design Not Requiring Magnet Operation

\$311 .23 Incl. GST

- Stainless Steel Wetted Parts
- 3/4" BSP Inlet

19DEF-050L

PW

- Design Working Pressure 50 psi (3.45 bar)
- Designed for User Comfort
- Meets ISO 22241 Requirements



Manual Nozzle - SELF 2000

- Flow Rate Up to 150 L/min
- 25mm Od Spout
- Maximum Efficiency Due to Low-Flow Resistance and Wide Range of Applications
- Supplied with Removable Lever Protection and Connectors
- Aluminium Body and Viton Seal
- 1" BSP with Swivel



OPW Automatic Nozzle - 7HB

- High Quality OPW High Flow Diesel Nozzle
- Flow Rates Up to 200 L/min
- 1" BSP Inlet
- East to Use - Utilising Accu-Stop Precise Flow Control Technology
- For Heavy-Duty, High-Flow Truck, Bus and Fleet Service
- Automatic Shut Off

ZVA4.0AB-F

\$1,001-68 Incl. GST **ELAFLE**

Automatic AdBlue Nozzle

- Automatic Shut Off 1" F BSP
- SS Wetted Parts
- Max Flow Rate 40 L/min
- Suitable for Urea (DEF) and Water
- Spout with Magnetic Opening
- Must be Used with Magnetic Adaptor
- With Integrated Misfilling Prevention

ZVA25-4.1 ELAFLEX

Automatic Nozzle - High Flow 1" c/w Swivel

Heavy Duty

BSP

34" M x 1" F BSP

360 Degree Swivel

Buna-N and Viton O-rings

Aluminium Body Construction

- High Flow Nozzle 1 c/w Swivel
- Automatic Shut Off
- Max Flow Rate: 140 L/min
- Suitable for All Fuels

ZVA24.1 \$507.32 ELAFLEX

Automatic Nozzle - Low Flow 3/4" c/w Swivel

- Low Flow c/w Swivel
- 1" BSP
- Slim Line Design with Automatic Shut Off
- Max Flow Rate: 80 L/min
- Integrated Swivel
- Approved for Resale Use
- Suitable for Petrol, Diesel, Ethanol Fuels and Biodiesel



Swivel Straight 1" BSP

- Heavy Duty Single Plane Swivel
- Full Circle Swivel Reduces Physical Strain on Nozzle & Hoses
- Stainless Body for Long Life
- Suitable For Diesel, Petrol and Fuel Oils
- 1" Male + Female BSP

FOLLOW US ON

\$84.63

Our Accessories Range Has Been Built to Supply **Options That Can** Maximise Safety and Convenience.



@liquipvictoria

Approved for Resale Use

Swivel Joint - ³/₄" M x 1" F

Reduces Strain on Hoses and Nozzles

Suitable for Diesel, Petrol and Fuel Oils

\$623.70 Incl. GST



LV-F0075023B

\$1,278.60 Incl. GST

Automatic Rewind Hose HD Reel - 1" x 10m

For Diesel and Oil

- Heavy Duty Rewind Mechanism and Steel Hub
- Easy & Versatile Installation
- Available in 3 Sizes: Small, Big and XL
- Protective Covers with 1" Inlet Swivel
 Includes 10 Metres x 1" Fuel Delivery H
- Includes 10 Metres x 1" Fuel Delivery Hose with 1" BSP Connections



Automatic Hose Reel c/w Hose HD - 1" x 15m

- Includes 15 Metres x 1" Fuel Delivery Hose with 1" BSP Connections
- For Diesel and Oil
- Sturdy Structure
- Corrosion Resistance
- Heavy Duty Conditions
- Can be Installed on Roof, Wall or Ground



LV-F0075007C



AdBlue Rewind Hose Reel

- Heavy Duty Spring Rewind with Hose Guides
- Build-In Hand Protection
- Automatic Hose Reel with 8 Metre Hose
- 3/4" BSP Male Ends
- Complete with Swivel and Elbow
- Reduces Pressure Loss
- Latch Mechanism Protector
- For AdBlue, DEF or Urea



\$905.25

Self Service Management 2018 Software

Up to 16 Dispensers

PIUSI

- USB Software Version (Web Version Also Available LV-F00773210)
- Users Management
- Transaction Reports
- Features Include Managing Devices, Choosing What to Report and Exporting in Your Preferred File Format

V-F00611D00

\$360.80 Incl. GST

Piusi 3D AdBlue Filter

- Prevents the Contamination of AdBlue During Transferring Operation
- 3-Step Filtration
- Hi-Resistance Case

PIUSI

- Removable Cartridge
 Transparent Container
- 1" BSP
- Max Flow Rate: 40 L/min
- 200 Micron Filtering Capacity

Dispensing Crimped Hoses

- ► Hose Parker 25mm / 1" ID
- > 2m, 4m, 8m and Cut Lengths Available
- Crimped Ends with 1" Male BSP
- Diesel Applications
- Bowser, Chemical, AdBlue, Petrol and Others Available

LV-F08977020: 4m x 1" Other sizes and cut LV-F16353000: 8mtr x 1" lengths available

<u>Automatic Tank</u> <u>Gauge (ATG)</u>

Eliminate Daily Dipping of Your Storage Tank and Streamline Your Refilling Process.

LV-ATG12V

Fuelcraft 12V \$1,320^{.00} Automatic Tank Gauge

- Eliminate Manual Dipping of Tank
- Compact, Install in Tanks Up to 4m High
- Remotely Read on Website Portal
- FREE Web Portal Access Included
- Low Level E-mail Alert System
- Integrated SIM Card
- For Diesel, Water, AdBlue, Lubricants, Chemicals



- For Use with Diesel, AdBlue, Water, Oil and Biodiesel
- Probe Tube Length: 10 Metres
- Maximum Measurable Length: 4 Metres
- Can Receive Quantity Pulses for Flow Metres
 Permits the Connection of Two Alarm or Lock
- Devices

www.liquipvictoria.com.au

LGT1 to LGT10

<u>(SBT's)</u>

SBT Cubes

Six Standard Sizes Ranging from 1,000 L to 10,000 L

Self Bunded Tanks

0

LGT300001 CK FILL 3000 LI

NO WELDING

LIQUIP

VICTORIA

- Manufactured to UL142, AS1940, AS1692, AS1657
- Off Grid Solar Powered Pump Packages - Up to 80 L/min
- Mains Power 240V or 12V Pump Packages - Up to 100 L/min
- Stackable and Movable Design
- **Custom Fuel Management Packages**

POA

- Also Can be Fitted Approved to Safely Store and Dispense
 - Diesel, Unleaded & Leaded Fuels, Oil, Food Stuffs, Chemical and Lubricants
- Transportable with Lockable Cabinet on the Front
- Custom Designed Dispensing System can be Fitted to Your Host Cube of Choice

Cube Tank Model	Safe Fill Capacity (Litres)	Tank Length (metres)	Tank Width (metres)	Tank Height (metres)	Empty Tank Weight (kg)	Dispensing Options
LC 1	1,000	1.645	1.100	1.270	710	Pump Bay
LC 2	2,000	2.215	1.425	1.270	1,010	Pump Bay
LC 3	3,000	2.135	2.185	1.270	1,295	Pump Bay
LC 4.5	4,500	2.925	2.200	1.270	1,570	Pump Bay
LC 6	6,000	3.815	2.200	1.270	2,030	Pump Bay
LC 10	10,000	6.060	2.440	1.295	4,445	Pump Bay



SBT-12 to SBT-110

SBT ISO Classic

- Multiple Storage Sizes Ranging from 12,000 L to 115,619 L
- Built to UL142, AS1940, AS1692, AS1657
- Durable, Modular and Robust Container Based Design
- Greater Usable Fuel Volume than Many Similar Tanks
- Overfill Valve, Anti-Syphon Valves and High Level Alarms are Supplied as Standard on all Tanks

POA

- Choice of Different Pumps, Fuel Management Systems (FMS), Bulk Dispensing Equipment, Tank Gauges and Meters Available
- Approved to Safely Store and Dispense Diesel, AdBlue, Diesel/AdBlue, ULP, Aviation, Oil & Other Petrochemicals
- Pump Flow Rates: 40 800 L/min

AN AND N

FLAMMABLE LIQUID

PETROL

Fuel Management Packages can be Custom Fitted

in

0

CLASS C1

CONSISTRATION IN DESTREM

LIQU

Ideally Suited For Use in Industries Such as: Fuel Distribution, Mining, Aviation, Power Generation, Oil and Gas, Military, Transport and Construction

Tank Model	Maximum Capacity (Litres) (nominal)	Safe Fill Capacity (Litres)	Tank Length (metres)	Tank Width (metres)	Tank Height (metres)	Empty Tank Weight (kg)	Dispensing Options	Liquid Storage Solutions
LFT12	12,000	11,240	2.991	2.438	2.896	4,300	Pump Bay	Diesel or ULP
LFT30	30,500	29,350	6.058	2.438	2.896	6,950	Pump Bay	Diesel or ULP
LFT30DA*	24,200/4,740	22,990/4,500	6.058	2.438	2.896	8,169	Pump Bay	Diesel/DEF
LFT68	69,000	65,570	12.192	2.438	2.896	12,750	Pump Bay	Diesel or ULP
LFT68DA*	59,840/7,350	56,995/6,662	12.192	2.438	2.896	15,715	Pump Bay	Diesel/DEF
LFT80	81,500	78,811	14.630	2.438	2.896	14,910	Pump Bay	Diesel
LFT100	101,192	96,132	14.630	2.438	3.200	17,100	No Pump Bay	Diesel
LFT110	115,619	109,838	14.630	2.438	3.550	19,100	No Pump Bay	Diesel





LIOUIP VICTORIA



When You're Looking to Safely Store and Dispense AdBlue, Liquip Victoria Can Assist With a Cost Effective, Custom Designed, Certified Self Bunded Tank Solution.

AdBlue SBT

IN CORE AS AD

LIQUIP

VICTORIA

- Available in Five Industry Preferred Sizes, Ranging from 3,000 L to 20,000 L (including a 10,000 L Slimline)
- ► Insulated Internal Stainless Steel Allows for a More Consistent Regulated Temperature
- Variety of Quality Pump Dispensing, Meters and Fuel Management Systems (FMS) can be Custom Fitted
- Approved to Safely Store AdBlue (DEF)
 Dispensing Pump Solutions: 40 – 800 L/min
- Stackable and Movable Design
 Designed to
- AS1940 and Built to AS1692

(DEF)	Tank Model	Capacity (Litres)	Length (metres)	Tank Width (metres)	Height (metres)	Tank Weight (kg)	Dispensing Options
- 800	Т3	3,000	2.752	1.130	2.566	1800	Pump Bay
d ign Built	T5	5,400	4.053	1.140	2.550	2360	Pump Bay
	T10	11,500	3.960	2.266	2.504	3205	Pump Bay
	T10 Slimline	10,000	6.850	1.220	2.500	3710	Pump Bay
	T20	20,000	6.960	2.250	2.500	5100	Pump Bay

POA

Liquip Rural Tanks and Trailers



CONTACT US: 03 9311 7822

sales@liquipvictoria.com.au

www.liquipvictoria.com.au

d h

-

LIQUIP

RUR

POA

AUSTRALIA

1

Australian Designed, Made and Manufactured.

A Simple and Easy to Use Fuel Dispensing System, That Safely and Efficiently Transports Fuel to Where It's Needed.

LIQUIP

Liquip Rural Refuelling Farm Trailers

- Heavy Duty Australian Made Steel Plate Tank with Baffles
- Available in 1,000 L, 1,250 L and 2,100 L Capacities
- Safely and Efficiently Transports Fuel
- Robust Chassis for On and Off-Road Use
- Built to Withstand Demanding Australian Work Environments and Conditions
- ▶ Hydraulic Brake System (Upgradeable to Electric) as Standard
- Top Tank Fill Point with Camlock Adaptor & Cap
- Spare Wheel Mounted To Rear of Trailer
- Comes Standard with Either a Petrol or 12V Pump Package that Includes the Pump, Meter, 10 Metre Hose Reel, Auto Nozzle (with Holster) and Fuel Filter - All Securely Fitted to the Trailer
- Refuelling Tank Trailers can be Customised with Multiple Options

COMING SOON



Various Sizes Will Be Available

- Various Packages
- Range of Designs

FOLLOW US ON

Bottom Fill Connection

@liquipvictoria

- Sight Tube
- Sturdy Frame

AUSTRALIAN MADE IN DERRIMUT, VICTORIA



CONTACT US



476 Boundary Road, Derrimut, VIC, 3026



03 9311 7822



www.liquipvictoria.com.au



Liquip Rural, located in Derrimut, VIC, is focused on advancing Australian design, manufacturing and productivity through the development and supply of quality products.

Follow Us For Updates:





@liquip-victoria



@liquipvictoria

TERMS AND CONDITIONS All prices include GST and are subject to change without notice. Specifications and descriptions are nominal and are to be used only as a guide. All items are subject to change due to product developments or variation in supply. Trademarks are the property of their respective owners. Our Standard Terms and Conditions of Sale apply to all products offered for sale. Prices only valid while current stocks last. Some images displayed show additional equipment to explain use and may not be included in the price. © Copyright 2021

SOLUTION FOCUSED. SERVICE DRIVEN.