Customer Form



Customer Name:					Delive	ry: [Stor	e 🗆 l	Pickup	□ T	o Site	□ Pa	llet
Delivery Address:													
Site Contact Name:		Site Contact Mobile:											
Date: / / Date Required: / / (Minimum 15 working days from date of order)		•											
1. STRUCTURE	I	5. L <i>A</i>	AYOUT	PLAN	NER								
Shed Type:		0m	ı 0 <u>.</u> 8	3 1.5	53	2.27	3.02	3.76	4.50	5.25	6.0	6.76	7.49
Model Number:		0m —											
Roof Type	Wall Height	0.78											_
☐ Flat Roof	□ 1.83m												
☐ Skillion Roof	□ 1.96m	1.53											
☐ Gable Roof	□ 2.10m												
	☐ Customm	2.27											
2. ANCHORING METHOD	Shed must be anchored	3.02											
☐ Into concrete - Anchor Kit N2													
☐ Into concrete - Anchor K	(it N3 (costal areas)	3.76											
☐ Into earth - Anchor Peg Kit N2 (qty)											e standard within th		
		In	betwee	n positio	ons ma	ay ava	ilable b	ut at an	addition	nal cost	. Please u	se the	
3. COLOUR				icons wh ories req		awing	plans	to clearly	/ identify	y any ac	ditional	options	
Panel													_
☐ ZINCALUME® steel (standard)	Trim and Channel ☐ Match trim and channel			Single Do 0.78m	oor			Wide Sing up to 1.2				Double up to 1	
□ Woodland Grey®	to COLORBOND® steel			CI: I: D									
☐ Monument®	☐ Galvanised	_	_	Sliding De 0.78m	oor	_	_	Double S Door 1.55)	XXXXXX	Aviary Section	
☐ Pale Eucalypt®													
☐ Classic Cream™		_		Sliding W 900x900	'indow	E		5 Blade L Window	ouvre			Skyligh	it
□ Paperbark®							_						
☐ Monument® MATT*	*Platinum range only			Wall Ven	t		\otimes	Whirly Bir	rd				
4. OPTIONS AND ACCESSORIES		Ac	dditional	l order o	details:	:							
Doors	Window	_											
□ Standard	□ Louvre 700x900												
□ Wide	☐ Sliding 900x900												
□ Sliding	☐ Skylight	_											
☐ Double: ☐ 1.5m ☐ 2.4m	Flooring	_											
☐ Roller door ☐ Auto Power Drive ☐ Bluetooth	☐ Galvanised C-channel Termi-Flooring												
☐ Door in Skillion	☐ Concrete		EASE N										
□ Door in Gable	☐ Galvanised Ramp										r if this is o uardian sh		
☐ 3 Point High Security	☐ Concrete Ramp	• ^	Skylight	placed in	a Gab	le roof	shed, o	overs 1 s	heet wid	ths from	ridge to w	,	
☐ Magnetic Door Holder	·	• #-	Timber F	Flooring	up to 3	3m x 3	m with	C Sectio	n galvani	ised.			
□ Rigid Door Holder											nited. ™ colou I rights reserv		

☐ Rigid Door Holder



- Australian COLORBOND® steel .35mm BMT supplied by BlueScope
- 20 year Structural Warranty, N2 Wind Rating (N3 available)
- Galvanised .55mm BMT Heavy Duty Trim to provide extra strength to the panels, as well as a matching COLORBOND® steel option
- Reinforced door no need for cross bracing
- Wall heights available: 1.83m, 1.96m, 2.09m, custom wall height available on request
- Available in a range of COLORBOND® steel colours
- Custom sizes available
- T-Bar handle as standard on all sheds













*Available on request

COLORBOND®, ZINCALUME®, BlueScope and ® colour names are registered trade marks of BlueScope Steel Limited. TM colour names are trade marks of BlueScope Steel Limited. The COLORBOND® steel colour swatches and images shown have been reproduced to represent actual product colours as accurately as possible. However, we recommend checking your chosen colour against an actual sample of the product before purchasing, as varying light conditions and limitations of the printing process may affect colour tones. © 2020 BlueScope Steel Limited ABN 16 000 011 058. All rights reserved. NC1267_SEPT20

