

soilbond®

Dust Suppressant

- Naturally derived, water based organic emulsion
- Functions by binding the fine particles of soil to form a cohesive surface crust
- With on going applications, the crust is maintained to overcome traffic wear
- Each maintenance application adds to the existing crust
- Offers significant water savings
- Lowered maintenance cost
- Improved wet strength
- Spray on application
- Easy and safe to apply
- Non slippery surface
- Ideal for driveways, car parks, paths, tracks, construction sites, trafficked and non-trafficked areas and more
- Available in 20 litres, 200 litres or 1000 litre IBC
- Environmentally friendly, non-harmful
- Made in Australia



Ph: 1300 764 526

sales@soilbond.com.au www.soilbond.com.au

Dust Suppressant

Application Guidelines

Mixing Ratio:	Mix 1 Litre of Soilbond into 9 Litres water = 10 Litres of diluted solution
Coverage:	Apply 2 Litres of diluted solution to each 1 m ²
Applications:	Treatment is achieved with a simple two-stage process: * First Stage: Crust formation - 1 - 2 applications as required * Second Stage: Crust maintenance - subsequent treatments as required
Equipment:	Water cart with controlled spray bar, bitumen sprayer or hand operated spraying system

Coverage Table

Soilbond (Litres)	Water (Litres)	Diluted Mixture	Coverage (m ²)
20	180	200	100
100	900	1000	500
200	1800	2000	1000
400	3600	4000	2000
600	5400	6000	3000
800	7200	8000	4000
1000	9000	10000	5000

1 litre Soilbond A02 Dust Suppressant therefore covers 5 m².

Available in 20 litre cubes, 200 litre drums or 1000 litre IBC's

Ph: 1300 764 526

sales@soilbond.com.au www.soilbond.com.au