



Heavy Duty PVC Corrugated Conduit

ALCCCH RANGE



ALCCCH2550SOLAR



Conforms to
AS/NZS
61386.22:2022
3.3.2.1




6J IMPACT
RESISTANCE



1250N
COMPRESSION
STRENGTH



EXTREME
UV
STABILISED



-5°C to 60°C
TEMPERATURE
RANGE



Pb
LEAD
FREE



25
YEAR
LIMITED
WARRANTY

FEATURES

- Highly flexible and lightweight PVC corrugated conduit for the protection of electrical wiring
- Heavy duty for indoor and outdoor applications
- Ribbed corrugated design allows easy installation in tight spaces
- Suitable for Industrial, residential and commercial projects
- It shields cables from mechanical stress (crushing, impact), dirt, dust, and moisture
- Conforms to AS/NZS 61386-22.2022 4.4.2.1 specifications
- UV stabilised

Operating Temperature: -5°C to +60°C

SPECIFICATIONS

PART NO.	CONDUIT SIZE		COLOUR
	DIAMETER	LENGTH	
ALCCCH2010	20mm	10m	Orange
ALCCCH2020	20mm	20m	Orange
ALCCCH2510	25mm	10m	Orange
ALCCCH2520	25mm	20m	Orange
ALCCCH3210	32mm	10m	Orange
ALCCCH3225	32mm	25m	Orange
ALCCCH4010	40mm	10m	Orange
ALCCCH4025	40mm	25m	Orange
ALCCCH5010	50mm	10m	Orange
ALCCCH6310	63mm	10m	Orange
ALCCCH2550SOLAR	25mm	50m	Grey