



Shotcreting since 1970



Polyurethane Shotcrete Nozzles System



Interchangeable Depth Gauges

✓ SAFETY ✓ PERFORMANCE ✓ QUALITY



100% Proudly Australian owned

(02) 4972 6886 0411 348 283 Unit 8/20 Mayfair Close, Morisset, NSW, 2260
groundsupportcontractors.com.au info@goundsupportcontractors.com

Universal Mounting Pipe



Comes in two sizes - 2" inch (50mm) & 2 1/2" inch (63mm) and takes up to a 3" hose

Universal Mounting Pipe bolts onto the boom with multi hole configurations to suit both Normet & Jacon machines

Has mounts for the Air V Block and the Hydrascaler, which simply bolts on making the installation / change over time being only minutes

The safety chain which is already attached to the Universal Mounting Pipe, connects with a carabiner to the GSC Nozzles safety lug

European Mounting Pipe



One size of 2 1/2" inch (63mm), and takes up to a 3" hose

European Mounting Pipe bolts on to the boom with hole configurations to suit Normet ONLY

Time frame and cost saver as no workshop time is needed for modification to fit the Normet machines

Has mounts for the Air V Block and the Hydrascaler, which simply bolts on

The safety chain which is already attached to the European Mounting Pipe, connects with a carabiner to the GSC Nozzles safety lug



Polyurethane 3 Part Nozzle System

Easy to clean polyurethane, a light tap and flush with water or air will keep the unit clean all shift

Nozzle

Wear limit ring on outlet

Average wear factor : 140m3



Nozzle safety lug has D-shackle to attach to the safety chain of GSC Mounting Pipe

Designed to blow off when blockage occurs, easy to retrieve with safety chain attached

Available in two sizes- 2" inch (50mm) & 2 1/2"inch (63mm)

Nozzle Outer Body

Light weight thus less strain on boom movements



Average wear factor : 500m3

Available in two sizes- 2" inch (50mm) & 2 1/2"inch (63mm)

Comes with hose clamps attached

Nozzle Inner Body

Clear polyurethane compound for ease of viewing blockages



Average wear factor : 200m3

Available in two sizes - 2" inch (50mm) & 2 1/2"inch (63mm)

GSC Dust Cap is a protective delivery line cover

Unscrew the Nozzle only and screw the Dust Cap directly into the Outer Body with the Inner Body in place




Attach the load rated safety chain that is supplied with the GSC Mounting Pipe onto the Dust Cap safety lug supplied

The safety chain is always attached prior to use

Precise safety limits are stamped on the unit

Twist valve to realise pressure



Interchangeable Depth Gauges

A Base Plate with individual 25mm Depth Gauge Extensions that interlocks on top of each other to get the required thickness depth



The Spigget can be exposed once shotcrete has been poured to indicate correct depth

Our Depth Gauges & base plates come in safety yellow only



Depth ranges from 50mm up to 125mm